

Equinox Tones 3850 (Impervious Aqua Bac)

Data Sheet: DOC3850v2 01.11.2015

NBS SPECIFICATION

M50 Rubber/Plastic/Cork/Lino/Carpet Tiling/Sheeting 170 Carpeting

Manufacturer	danfloor Uk Limited, 106 Longmead Road, Emerald Park, Emersons Green, Bristol, BS16 7FG Tel: 0333 014 3132, Fax: 0333 014 3134 Website: www.danfloor.co.uk, Email: sales@danfloor.co.uk
Reference	Equinox Tones 3850
Backing	Impervious Aqua Bac
Protection	Mædical i-Link Anti Bacteria

DETAILED SPECIFICATION

Manufacturer	danfloor Uk Limited, 106 Longmead Road, Emerald Park, Emersons Green, Bristol, BS16 7FG Tel: 0333 014 3132, Fax: 0333 014 3134 Website: www.danfloor.co.uk, Email: sales@danfloor.co.uk
Reference	Equinox Tones 3850
Backing	Impervious Aqua Bac
Construction	1/10 th Gauge Tufted Cut Pile
Surface Yarn	100% PRISM SD Heat Set Twist
Pile Weight	1100 g/m ²
Total Product Weight	3150 g/m ²
Dimensions	4.00 Mts wide
Pile Height	5.00mm
Protection	Mædical i-Link Anti Bacteria (4 Log 99.99)
Total Carpet Thickness	10.00mm
Colours	Available in 30 colours
Warranties	10 year wear warranty, 10 year anti-static warranty Full warranty details available on request
Breeam Certification	Cert ENP 511 Domestic (Multi residential) A BRE rating, Healthcare A+ BRE rating, Education A BRE rating.

INSTALLATION INSTRUCTION

Recommended adhesive. F.Ball & Co. 01538 361633. Product - Permanent Bond F3, F40 or S910. Seaming F30.

All carpets should be laid in accordance with BS5325:2001 Installation of textile floorcovering.